

COMPOSITION	Polydimethylsiloxane emulsion							
IONIC TYPE	Nonionic							
APPEARANCE	White, slightly viscous liquid							
PROPERTIES	<p>MEGSOL SKK is a very effective antifoamer used in sizing, bleaching, dyeing, finishing baths and printing pastes.</p> <p>Can easily be diluted with soft water.</p> <p>Can be used together with anionic and cationic substances.</p> <p>Can be used in biological refineries with giving no harm to bacteria.</p> <p>Eliminates foam problem in preparing printing paste.</p>							
APPLICATION	<p>It should be diluted with soft water in ratio 1/5 – 1/10.</p> <p>If it is used in the diluted form, the daily solution should be mixed every time.</p> <p>The application amount is determined according to the foam formation of other chemicals.</p> <table><tr><td>Exhausting Process</td><td>0.01-0.07 g/l</td></tr><tr><td>Foulard</td><td>0.1- 0.35 g/l</td></tr><tr><td>In refinery</td><td>Diluted with water in a ratio 1/10</td></tr></table>		Exhausting Process	0.01-0.07 g/l	Foulard	0.1- 0.35 g/l	In refinery	Diluted with water in a ratio 1/10
Exhausting Process	0.01-0.07 g/l							
Foulard	0.1- 0.35 g/l							
In refinery	Diluted with water in a ratio 1/10							
PACKING	60 kg plastic drum and 200 kg barrel.							
STORAGE	It is advised to be stored in closed vessels. It must be protected from excessive cold and heat. Besides the lid of plastic drum has to be kept closed.							